

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Original) A disk controller for controlling reading and writing of data from and to a disk, comprising:

a first terminal used to output a first write gate signal which dictates writing of data to the disk;

a second terminal used to input a second write gate signal output from an external circuit, the external circuit performing predetermined signal processing on write data in accordance with the first write gate signal output from the first terminal, and outputting the second write gate signal, the second write gate signal reflecting a signal delay in the predetermined signal processing; and

a write inhibition controller which monitors the second write gate signal input via the second terminal, and detects, as a write inhibition state, a state in which writing of data to the disk is dictated during a period in which writing of data to the disk should be inhibited.

2. (Original) The disk controller according to claim 1, wherein:

the external circuit is a signal processing circuit, the signal processing circuit performing the signal processing on write data in accordance with the first write gate signal output from the first terminal, and outputting the processed write data to a head amplifier circuit, the signal processing circuit also outputting the second write gate signal, a period in which the second write gate signal is valid being longer, by a time corresponding to a delay time in the predetermined signal processing, than a period in which the first write gate signal is valid, the head amplifier circuit causing a head to read or write data from or to the disk; and

the second terminal is used to input the second write gate signal output from the signal processing circuit.

3. (Original) The disk controller according to claim 2, further comprising a read/write controller which outputs a third write gate signal, together with the write data used in the predetermined signal processing by the signal processing circuit, the third write gate signal being used as the first write gate signal output from the first terminal.

4. (Original) The disk controller according to claim 3, wherein the write inhibition controller outputs the second write gate signal as a fourth write gate signal in a normal state, without changing a state of the second write gate signal, the write inhibition controller negating the second write gate signal and outputting the negated second write gate signal as the fourth write gate signal in the write inhibition state, the fourth write gate signal being used to instruct the head amplifier circuit to write data to the disk.

5. (Original) The disk controller according to claim 4, further comprising a third terminal used to output, to an outside of the disk controller, the fourth write gate signal supplied from the write inhibition controller.

6. (Original) The disk controller according to claim 5, wherein the third terminal is used to output, to the head amplifier circuit, the fourth write gate signal supplied from the write inhibition controller.

7-16. (Cancelled).

17. (Original) The disk controller according to claim 1, wherein the disk is provided with a plurality of servo areas extending radially at circumferentially regular intervals, and a period in which writing of data to the disk should be inhibited corresponds to a period in which a head is passing through one of the plurality of servo areas.

18. (Original) The disk controller according to claim 1, wherein the disk is rotated by a spindle motor, and a period in which writing of data to the disk should be inhibited corresponds to a period in which a rotational speed of the spindle motor is in a non-steady state.

19. (Original) A disk drive comprising:
a disk controller for controlling reading and writing of data from and to a disk, the disk controller including:
a first terminal used to output a first write gate signal which dictates writing of data to the disk;

a second terminal used to input a second write gate signal;
a read/write controller which outputs, together with write data, a third write gate signal used as the first write gate signal output through the first terminal;
a third terminal used to output a fourth write gate signal to an outside of the disk controller; and
a write inhibition controller which monitors the second write gate signal input via the second terminal, and detects, as a write inhibition state, a state in which writing of data to the disk is dictated during a period in which writing of data to the disk should be inhibited, the write inhibition controller outputting the second write gate signal as the fourth write gate signal in a normal state without changing a state of the second write gate signal, the write inhibition controller negating the second write gate signal and outputting the negated second write gate signal as the fourth write gate signal in the write inhibition state;
a signal processing circuit connected to the disk controller via the first and second terminals of the disk controller, the signal processing circuit performing predetermined signal processing on write data in accordance with the first write gate signal output through the first terminal, and outputting the second write gate signal, a valid period of the second write gate signal being longer than the first write gate signal by a time corresponding to a delay time in the predetermined signal processing; and
a head amplifier circuit which causes a head to write, to the disk, the write data processed by the signal processing circuit in accordance with the fourth write gate signal output through the third terminal of the disk controller.

20. (Original) A method of controlling inhibition of writing of data to a disk, for use in a disk drive in which reading and writing of data from and to the disk is performed using a head under control of a disk controller via a signal processing circuit and a head amplifier circuit, the method comprising:

outputting a first write gate signal and write data from the disk controller to the signal processing circuit, the first write gate signal instructing the signal processing circuit to write the write data;

performing predetermined signal processing on the write data in accordance with the first write gate signal output from the disk controller to the signal processing circuit;

outputting a second write gate signal corresponding to the first write gate signal from the signal processing circuit to the disk controller, the second write gate signal reflecting a signal delay in the predetermined signal processing;

detecting, as a write inhibition state, a state in which an instruction to write data to the disk is issued during a period in which writing of data to the disk should be inhibited, in accordance with the second write gate signal output from the signal processing circuit to the disk controller; and

outputting, from the disk controller to the head amplifier circuit, the second write gate signal as a fourth write gate signal in a normal state, without changing a state of the second write gate signal, the fourth write gate signal instructing writing, to the disk, of the write data processed by the signal processing circuit; and

negating the second write gate signal in the write inhibition state, and outputting, from the disk controller to the head amplifier circuit, the negated second write gate signal as the fourth write gate signal in the write inhibition state.